



## DIRECTIONAL CONTROL VALVES CETOP 3/NG6

### INTRODUCTION

The ARON directional control valves NG6 are designed for subplate mounting with an interface in accordance with UNI ISO 4401 - 03 - 02 - 0 - 94 standard (ex CETOP R 35 H 4.2-4-03), and can be used in all fields on account of their high flow rate and pressure capacities combined with compact overall dimensions.

The use of solenoids with wet armatures allows a very practical, safe construction completely dispensing with dynamic seals; the solenoid tube is screwed directly onto the valve chest whilst the coil is kept in position by means of a lock nut.

The special, precise construction of the ports and the improvement of the spools enables relatively high flow rates to be accommodated with a minimal pressure drop ( $\Delta p$ ).

The operation of the directional valves may be electrical, pneumatic, oleodynamic, mechanical or lever.

The centre position is obtained by means of calibrated length springs which reposition the spool in the centre or end of travel position once the action of the impulse is over.

The solenoids are constructed with a protection class of IP66 to DIN 40050 standards and are available in either AC or DC form in different voltage and frequencies.

The new type DC coil "D15", of cause their high performance, allows to increasing the limits of use respect to last series.

All types of electrical control are available, on request, with different types of manual emergency controls.


The solenoid coils are normally arranged for DIN 43650 ISO 4400 type connectors; is available on request these variant coils: with AMP Junior connections, with AMP junior and integrated diode, with Deutsch DT04-2P connections or solenoid with flying leads. Connectors with built in rectifiers or pilot lights are also available.

The valves are designed for use with DIN 51524 standard hydraulic mineral oils and it is recommended that filters should be fitted to ensure a maximum contamination level of class 10 in accordance with NAS 1638,  $\beta_{25} \geq 75$ .

### CETOP 3/NG06

STANDARD SPOOLS	CH. I PAGE 10
AD.3.E...	CH. I PAGE 11
AD.3.E...J*	CH. I PAGE 12
AD.3.V...	CH. I PAGE 13
AD.3.L...	CH. I PAGE 14
OTHER OPERATOR	CH. I PAGE 15
AD.3.P...	CH. I PAGE 16
AD.3.O...	CH. I PAGE 16
AD.3.M...	CH. I PAGE 17
AD.3.D...	CH. I PAGE 17
"D15" DC COILS	CH. I PAGE 18
"K12" AC SOLENOIDS	CH. I PAGE 18
STANDARD CONNECTORS	CH. I PAGE 19
"LE" VARIANTS	CH. I PAGE 20
L.V.D.T.	CH. I PAGE 21

### PRESSURE DROPS



The diagram at the side shows the pressure drop curves for spools during normal usage. The fluid used is a mineral oil with a viscosity of 46 mm<sup>2</sup>/s at 40°C; the tests have been carried out at a fluid temperature of 40°C. For higher flow rates than those in the diagram, the losses will be those expressed by the following formula:

$$\Delta p_1 = \Delta p \times (Q_1/Q)^2$$

where  $\Delta p$  will be the value for the losses for a specific flow rate  $Q$  which can be obtained from the diagram,  $\Delta p_1$  will be the value of the losses for the flow rate  $Q_1$  that is used.

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
01	5	5	5	5	
02	6	6	6	6	5
03	5	5	6	6	
04	1	1	1	1	4
44	1	1	1	1	2
05	5	5	5	5	
06	5	5	6	5	
66	5	5	5	6	
07		4	6		
08	6	6			
09		5		5	
10	5	5	5	5	
	Curve No.				

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
11	4			6	
22		4	6		
12		5		6	
13		5	6	6	
14	2	1	1	1	2
28	1	2	1	1	2
15 - 19	4	4	6	6	
16	5	5	4	4	
17 - 21	1	3			
18	5	5			
20	4	4	4	4	
	Curve No.				

ORDERING CODE

<b>AD</b>	Directional valve
<b>3</b>	CETOP 3/NG6
<b>E</b>	Type of operator For other operator see next pages
<b>**</b>	Spool see page I•10
<b>*</b>	Mounting type (table 1)
<b>*</b>	Voltage (table 2)
<b>**</b>	Variants (table 3)
<b>*</b>	Serial No.

**3** = DC voltage ("D15" coil)  
**2** = AC voltage ("K12" solenoid)

TAB.2 "E" OPERATOR TYPE

AC VOLTAGE	
<b>A</b>	24V/50Hz
<b>B</b>	48V/50Hz*
<b>J</b>	115V/50Hz - 120V/60Hz
<b>Y</b>	230V/50Hz - 240V/60Hz
<b>E</b>	240V/50Hz*
<b>F</b>	24V/60Hz*
<b>K</b>	AC without coils
DC VOLTAGE	
<b>L</b>	12V
<b>M</b>	24V
<b>V</b>	28V*
<b>N</b>	48V*
<b>Z</b>	102V*
<b>P</b>	110V*
<b>X</b>	205V*
<b>W</b>	DC without coils

115Vac/50Hz  
120Vac/60Hz  
with rectifier

230Vac/50Hz  
240Vac/60Hz  
with rectifier

Voltage codes are not stamped on the plate, their are readable on the coils.  
(\* ) Special voltage

TAB.1- MOUNTING

STANDARD	
<b>C</b>	
<b>D</b>	
<b>E</b>	
<b>F</b>	
SPECIALS (WITH PRICE INCREASING)	
<b>G</b>	
<b>H</b>	
<b>I</b>	
<b>L</b>	
<b>M</b>	

- AMP Junior coils (with or without diode) and coils with flying leads and coils type Deutsch, are available in 12V or 24V DC voltage only.
- The pastic type coil (BR variant) is available in 12V, 24V, 28V or 110V DC voltage only.

- **Mounting type D** is only for valves with detent
- In case of **mounting D** with detent a maximum supply time of 2 sec is needed (only for AC coils).

TAB.3 - VARIANTS

VARIANT	CODE	◆	PAGE
No variant	00		
Viton	V1		
Emergency control lever for directional control valves type ADC3 and AD3E	LE		I•20
Emergency button	E1		I•18
Rotary emergency button	P1		I•18
Rotary emergency button (180°)	P5		I•18
Pilot light	X1		I•19
Rectifier	R1		I•19
Preset for microswitch (E/F/G/H mounting only) (see below note ◊)	M1	◆	I•11- I•14
Solenoid valve without connectors	S1		
Marine version (AD.3.P..)	H1	◆	
Cable gland "PG 11"	C1		I•19
Emergency button+ Viton	EV		
Emergency button+ Pilot light	EX		
Viton + Pilot light	VX		
Emergency button+ Viton + Pilot light	A1		
Emergency button+ Rectifier	ER		
Viton + Rectifier	VR		
Viton + Rectifier + Emergency button	A2		
Pilot light + Rectifier	XR		I•19
Pilot light + Rectifier + Emergency button	A3		
Pilot light + Rectifier + Emergency button+ Viton	A4		
Preset for microswitch + Viton	MV	◆	
5 micron clearance	Q1	◆	
Spool movement speed control (only VDC) with ø 0.3 mm orifice	J3	◆	I•12
Spool movement speed control (only VDC) with ø 0.4 mm orifice	J4	◆	I•12
Spool movement speed control (only VDC) with ø 0.5 mm orifice	J5	◆	I•12
Spool movement speed control (only VDC) with ø 0.6 mm orifice	J6	◆	I•12
AMP Junior coil - for12V or 24V DC voltage only	AJ		I•18
AMP Junior coil and integrated diode - for12V or 24V DC voltage only	AD		I•18
Coil with flying leads (175 mm) - for12V or 24V DC voltage only	SL		I•18
D15 plastic type coil - for12V, 24V, 28V or 110V DC voltage only	BR		
Deutsch DT04-2P coil - for12V or 24V DC voltage only	CZ		I•18
IP67 type of connector	CN		I•19

Other variants relate to a special design

◊ = Maximum counter-pressure on T port: 8 bar  
◆ = Variant codes stamped on the plate