



"LE" VARIANT - EMERGENCY CONTROL LEVER FOR DIRECTIONAL CONTROL VALVES (ADC/AD.3.E)



The emergency control lever for solenoid valves by Aron, represents a develop in terms of safety and flexibility among applied hydraulic components.

Thanks to his flexibility, the component was designed to be inserted between the valve body and the spool, providing total interchangeability between the different types of solenoid body valves manufactured by Aron. It is compatible with the standard CETOP 3 and stackable valves with threaded connections –G3/8" or 9/16-18UNF (SAE 6). The component is available for both directional control and proportional valves (for the last type of control please consult our Technical Department)

As an emergency lever applied to solenoid valves, the control can be used as a safety device in conformity with the industry standards , also playing an useful role in the event of power cuts. The control can be used in agricultural and mobile fields; the manual action can be used to carry out periodic maintenance work on mobile components of the vehicle , in perfectly safe working conditions.

Max operating pressure port T:	
dynamic	160 bar
static	210 bar
Max operating pressure port P for series connection configuration	
	160 bar

- MOUNTING TYPE: C / F / H
- SPOOLS TYPE: 01/02/03/04/16/17/66

HYDRAULIC SIMBOL



MOUNTING COMPATIBILITY

CODE VALVE	DESCRIPTION	COIL	VOLTAGE
ADC.3...	Directional control valve	A09	27 W
AD.3.E...	Directional control valve	D15	30 W

OVERALL DIMENSION

